

DOUBLE SIDED TAPES 双面胶带



ITEM NO.	DESCRIPTION	THICKNESS (mm)	ADHESION (G/25mm)	TENSILE STRENGTH (KG/25mm)	ELONGATION (%)	FEATURES
产品番号	品名	厚度	粘着力	抗张强度	伸長率	特性/用途
YWT-001	Tissue Double Sided Tape 棉纸双面胶带	0.1	2800	2	5	Rubber based adhesive. Excellent for adhering on various kinds of foams, sponges & rough surfaces.
YWT-010	Tissue Double Sided Tape 棉纸双面胶带	0.1	1200	2	5	Solvent acrylic adhesive. Good adhesion power for nameplates, metal plates & other industrial uses.
YWT-0074Q	Tissue Double Sided Tape 棉纸双面胶带	0.09	1200	1.8	4	Solvent acrylic adhesive, very high bonding. For general applications in the industrial & commercial sectors.
YWT-2000	Tissue Double Sided Tape 棉纸双面胶带	0.09	1500	2	5	Water acrylic adhesive with good initial tack. Suitable for general bonding, mounting & fixing purposes.
YWT-010BK	Tissue Double Sided Tape 棉纸双面胶带	0.14	2000	2	5	UL recognized. Black tissue coated with blackened adhesive. Good for splicing, mounting, bonding, ...uses. Special adhesive for sticking on rubber material.
YWT-297	Polyester Double Sided Tape 聚脂薄膜双面胶带	0.09	1200	5	50	Moderate adhesive to most substrates. Ideal for bonding sporting goods, mounting for nameplates, signs, ... etc.
YWT-012	Opp Double Sided Tapes OPP双面胶带	0.1	1500	7.5	150	Transparent with synthetic resin adhesive. Good for joining, splicing, ... etc.
YWT-5254	Opp Double Sided Tapes (easy-tear) OPP双面胶带(易撕)	0.075	1200	2	100	Easy tear polypropylene film coated with rubber adhesive. Designed to make manual cutting easier.
YWT-0361Y	UPVC Double Sided Tape UPVC双面胶带	0.25	1500	15	50	High tack, Excellent adhesion to low energy surface like PE, PP, ... Also good shear & chemical resistant.
YWT-0532R	Reinforced PE Foam Double Sided Tape 补强PE泡棉双面胶带	1.00	1600	30	-	Good heat resistant. Ideal for industrial applications, window glazing, automotive side moulding, mounting, ... etc.

* Please contact our sales representative for special requirements which are not listed above

DOUBLE SIDED TAPES 双面胶带



ITEM NO.	DESCRIPTION	THICKNESS (mm)	ADHESION (G/25mm)	TENSILE STRENGTH (KG/25mm)	ELONGATION (%)	FEATURES
产品番号	品名	厚度	粘着力	抗张强度	伸長率	特性/用途
YWT-020A	PE Foam Double Sided Tape PE泡棉双面胶带	0.8	2000	-	-	Outstanding weather resistant, high crosslinking strength. Good for automotive & plastic strip mounting.
YWT-4315	EVA Foam Double Sided Tape EVA泡棉双面胶带	0.32	1500	-	-	High tack, good shear strength. Good for general purpose mounting, fixing, ... etc. Other thickness available.
YWT-5133	Cloth Double Sided Tape 布双面胶带	0.32	1200	-	-	Suitable for laying carpets in the exhibition stand. Easily removed & leaves no residue after peeling off.
YWT-2484	Transfer Tape 无基材胶带	0.1	1600	-	-	Pure acrylic, high shear strength & heat resistant. Good adhesion on rough, structured surfaces.
YWT-2485	Transfer Tape 无基材胶带	0.05	1300	-	-	Pure acrylic adhesive, high shear strength & heat resistant. Good adhesion on rough, smooth surfaces.
YWT-2568	Transfer Tape 无基材胶带	0.06	2500	-	-	Synthetic rubber adhesive with good shear strength. Good adhesion on metal, PS, UPVC & various types of foams.
YWT-1023	Finger Lifting Tape 手提易撕胶带	0.03	-	-	-	Good adhesion power. Ideal for padded mailing envelopes & other uses where instant bonding is required.
YWT-0217H	Sealing Tape 封口胶带	0.165	2500	-	-	Strong & permanent adhesion suitable for sealing envelopes containing confidential documents and courier bags.

* Please contact our sales representative for special requirements which are not listed above